9110FZ Oras Electra Safety Servantkran, 3 V, Bluetooth

Valid from 11/2023

EAN: 6414150102073
NRF: 4203765
static.oras.com/9110FZ



Electra 91 series is designed to compliment any new bathroom. The new sharp design give an illustration of the faucet leaning forward, but still give you good height to secure free space for the hands, in any given sink design.

Key Features
Aerator with Tilt function +/- 10° for more flexible installation
Newest Sensor technology for better detection and operation comfort
Bluetooth technology for easy adjustment to personalize settings
Antiscalding protection
Temperature measurement
Battery and power cable

- Servant
- Berøringsfri, Batteridrevet, Separat omformer, Bluetooth®, Blyfri
- Benkemontert
- Forkrommet
- Fast tut
- PCA® strålesamler med konstant vannmengde uavhengig av trykk, Justerbar vannstråle
- Temperaturreguleringshendel
- Justerbar varmtvannsbegrenser (ettermonterbar)
- Manuell blandeventil, Tilbakeslagsventil, Smussfilter
- Advanced PSD sensor, Signallys, Indikator for lav spenning
- Fleksible slanger
- 3S Installasjon

Teknisk data

Tekniske egenskaper

Varmtvannsforsyning	**max. +70°C**
Arbeidstrykk	**100 - 1000 kPa**
Tilkoblingsstørrelse	**G3/8**
Projeksjon	**123 mm**
Tilbakeslagssikring (EN1717)	**EB**
Materiale	**Composite**

Program instillinger


Etterrenningstid	**3 s (1-20 s)**
Automatisk spyling	**off (off/1-120 h)**
Automatisk spyling periode	**30 s (1-1800 s)**
Funksjonstid	**2 min (1 - 1800 s)**

Elektroniske attributter


Elektrisk tilkobling	**9 V**
Batteri	**AA 1.5 V Lithium x 2**
Bluetooth version	**5.x (D060576)**


Bestemmelser


EU Directive	**CE Radio Equipment Directive 2014/53/EU , Low Voltage Directive 2014/35/EU , EMC Directive 2014/30/EU , RoHS Directive 2011/65/EU**
EN Standard	**EN 15091, ETSI EN 301 489-1 V1.9.2 , ETSI EN 300 328 v2.2.2 , EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011+AC:2012 , EN 60335-1:2012+A11+A13+A1+A14+A2+A15:2021, Part 19.11.4**
Støyklasse	**I (ISO 3822)**
Tetthetsklasse	**IP 55**



© 2023 Oras Ltd. - www.oras.com - 02.09.2023







© 2023 Oras Ltd. - www.oras.com - 02.09.2023